

COMMERCIAL WATER FILTER SYSTEM 95 SERIES

95 systems are available in single tank configurations only.



Overview

Canature has dedicated professional engineers with decades of commercial water treatment experience. Over the years, they have built a reputation for designing efficient, high quality commercial water filter systems.

Our 95 Series filters provide high quality filtered water. The system is engineered and thoroughly tested to provide years of reliable, trouble free performance with a minimum of maintenance.

For Applications Such As

Apartments - Boiler Treatment - Cooling Towers - Motels - Schools - Nursing Homes - Car Wash - Dairies - Factories
Laundromats - Office Buildings - Resorts - Restaurants - RO Pre-treatment - Office Buildings - Hospitals

Operating Parameters

- Operating pressure: 20 - 125 psi
- Operating temperature: 39 - 100° F
- Electrical: Input 120V 60 Hz - Output 12V 650mA

Materials of Construction

- Control Valve: Plastic PPO (Noryl)
- Mineral Tanks: Corrosion resistant fibreglass reinforced polyethylene NSF 44 Certified
- Internal Distributors: Sch 80 PVC/ABS

Standard Features

- High Flow Rates: Feature 95 High Flow control valve backed by a full 5 year warranty.
- Large Display: Fully programmable and easy to set electronic controller.
- Tough Corrosion Resistant Pressure Vessels: NSF approved filament wound mineral tanks with rugged polyethylene liners backed by a 5 year warranty.
- Inlet / Outlet Service Connections 1" thru 1.5": Provides recommended service flow rates at minimal pressure loss.
- High Flow Distribution: Durable, non-corrosive ABS fine slotted hub and lateral distribution provides trouble-free operation.
- Advanced Diagnostic Information: Easily trouble shoot and access system information displayed in real time.

Optional Features

- No Raw Water Bypass: Easy to add external electric ball valve to prevent raw water bypass during regeneration.

Specifications (Figures are per tank)

MULTI-MEDIA FILTER

MODEL	TANK SIZE	SERVICE FLOW RATE PER TANK - GPM		MAX FLOW TO DRAIN - GPM
		Maximum	Typical	
CMM 10-1.5"	10x54	5	2.5	5
CMM 12-1.5"	12x52	7	3.5	7
CMM 14-1.5"	14x65	10.0	5.0	11
CMM 16-1.5"	16x65	14.0	7.0	17
CMM 18-1.5"	18x65	18.0	9.0	21
CMM 21-1.5"	21x62	24.0	12.0	24

CARBON FILTER

MODEL	TANK SIZE	SERVICE FLOW RATE PER TANK - GPM Typical	MAX FLOW TO DRAIN - GPM
CAC 10-1.5"	10x54	3	5
CAC 12-1.5"	12x52	4.5	7
CAC 14-1.5"	14x65	6.0	11
CAC 16-1.5"	16x65	8.0	14
CAC 18-1.5"	18x65	10.0	21
CAC 21-1.5"	21x62	14.0	24

GREENSAND FILTER

MODEL	TANK SIZE	SERVICE FLOW RATE PER TANK - GPM			MAX FLOW TO DRAIN - GPM
		0 - 3 PPM	3 - 8 PPM	8 - 15 PPM	
CMG 10-1.5"	10x54	2.5	1.5	1	5
CMG 12-1.5"	12x52	4	2	1.5	7
CMG 14-1.5"	14x65	5.0	3.0	2.0	11
CMG 16-1.5"	16x65	7.0	4.0	3.0	14
CMG 18-1.5"	18x65	9.0	5.0	3.5	21
CMG 21-1.5"	21x62	12.0	7.0	5.0	24

BIRM FILTER

MODEL	TANK SIZE	SERVICE FLOW RATE PER TANK - GPM Typical	MAX FLOW TO DRAIN - GPM
CBM 10-1.5"	10x54	2.5	5
CBM 12-1.5"	12x52	4.0	7
CBM 14-1.5"	14x65	5.0	11
CBM 16-1.5"	16x65	7.0	14
CBM 18-1.5"	18x65	9.0	21
CBM 21-1.5"	21x62	12.0	24

NUETRALIZER FILTER

MODEL	TANK SIZE	SERVICE FLOW RATE PER TANK - GPM		MAX FLOW TO DRAIN - GPM
		Maximum	Typical	
CNN 10-1.5"	10x54	2.5	1.5	5
CNN 12-1.5"	12x52	4.0	2.0	7
CNN 14-1.5"	14x65	5.0	3.0	11
CNN 16-1.5"	16x65	7.0	4.2	14
CNN 18-1.5"	18x65	9.0	5.0	21
CNN 21-1.5"	21x62	12.0	7.0	24

CMM FILTER (MULTI-MEDIA)

For removal of sediment, dirt and other forms of suspended matter. Provides particle filtration down to 10 micron with increased service flow rate per square foot bed area over traditional sand media filters. Media has excellent chemical properties—high silica content and low soluble calcium, magnesium and iron compounds.

CAC FILTER (ACTICATED CARBON)

For the reduction of tastes, odors and dissolved organic chemicals from municipal and industrial water supplies. The media has exceptionally high internal surface area with optimum pore size for the adsorption of a broad range of low molecular weight organic contaminants and oxidizing agents like chlorine and ozone.

CMG FILTER (GREENSAND)

For the oxidation and removal of iron, manganese, and hydrogen sulfide. Provides filtration level to 30 micron. Requires a potassium permanganate, chlorine, or other strong oxidant injection assembly to assist oxidative capacity of the filter media.

CBM FILTER (BIRM)

For the reduction of dissolved iron and manganese compounds. The Birm media is not consumed in the iron removal operation resulting in a low attrition loss. It has a wide temperature performance range and extremely high removal efficiency. The media does not require chemicals for regeneration and only periodic backwashing is required. Air injection may be required.

CNF FILTER (NUETRALIZER)

Raise the pH of acidic water to neutralize corrosiveness and protect fixtures, pipes and appliances.

Operating Parameters

- Operating pressure: 20 - 125 psi
- Operating temperature: 39 - 100° F
- Electrical: Input 120V 60 Hz - Output 12V 650mA



Novo Water Conditioning
Toll Free 1-877-655-6686
Fax 1-877-658-6686
support@novowater.com
www.novowater.com



We can manufacture to unique specifications or use our in-house engineering capabilities to develop a system to meet your specific requirements.