

NOVOSOFT 485HE SERIES WATER SOFTENER

Novo's premier high-efficiency softener sets the new standard for high performance while offering more features designed to make installations faster & easier than ever!




Uses up to
75% less salt
& **64% less water!!!**

Cabinet model

Twin tank model

Two piece cabinet design



Upflow regeneration saves salt by pushing the hardness minerals up & out to drain instead of down through the sodium-charged portion of the softener bed which needlessly depletes it.



IAPMO R & T Certified
against CSA B483.1

Features:

- ➔ Reverse Flow regeneration preserves unused portion of softening bed from unnecessary exchange saving salt
- ➔ Precision Brining calculates the exact amount of brine required to regenerate saving up to 30% more salt
- ➔ Automatic Backwash Frequency Preset for clean municipal water saves water by matching backwash to water quality need
- ➔ Soft Water Brine Tank Refill keeps tank & injectors clean
- ➔ Automatic System Refresh flushes stagnant water after 7 days of non-use preventing bacteria growth
- ➔ Soft Water Recharge Mode ensures soft water during unusually heavy water usage
- ➔ Compact two-piece cabinet or traditional twin tank
- ➔ Condensation tank jacket (8", 9" & 10" twin tank models)




7 Year Warranty
Control Valve



Lifetime Warranty
Pressure tank

Estimated Annual Back Wash
Water Usage





Choosing the Right Size Softener

SOFTENER SIZING GUIDE

Water Hardness	Grains Per Gallon
Very Hard	> 14
Hard	7.5 - 14
Moderate	3 - 7.5
Soft	< 3

# of People	Total Hardness (Grains per Gallon)									
	10	15	20	25	30	40	50	60	70	75
1	NVO485-75 EFT20	NVO485-75 EFT20	NVO485-75 EFT20	NVO485-75 EFT20	NVO485-75 EFT20	NVO485-100 EFT30	NVO485-100 EFT30	NVO485-150 EFT40	NVO485-150 EFT40	NVO485-150 EFT40
2	NVO485-75 EFT20	NVO485-75 EFT20	NVO485-75 EFT20	NVO485-75 EFT20	NVO485-75 EFT20	NVO485-100 EFT30	NVO485-100 EFT30	NVO485-150 EFT40	NVO485-150 EFT40	NVO485-150 EFT60
3	NVO485-75 EFT20	NVO485-75 EFT20	NVO485-75 EFT20	NVO485-75 EFT20	NVO485-75 EFT20	NVO485-100 EFT30	NVO485-150 EFT60	NVO485-150 EFT60	NVO485-200 EFT60	NVO485-200 EFT60
4	NVO485-75 EFT20	NVO485-75 EFT20	NVO485-75 EFT20	NVO485-75 EFT30	NVO485-100 EFT30	NVO485-150 EFT60	NVO485-150 EFT60	NVO485-200 EFT90	NVO485-300 EFT90	NVO485-300 EFT90
5	NVO485-75 EFT20	NVO485-75 EFT20	NVO485-100 EFT30	NVO485-100 EFT40	NVO485-150 EFT60	NVO485-150 EFT60	NVO485-200 EFT90	NVO485-300 EFT90	NVO485-300 EFT90	NVO485-300
6	NVO485-75 EFT20	NVO485-75 EFT30	NVO485-100 EFT40	NVO485-150 EFT60	NVO485-150 EFT60	NVO485-200 EFT90	NVO485-300 EFT90	NVO485-300 EFT90	NVOHEDP-300	Call for Sizing
7	NVO485-75 EFT20	NVO485-75 EFT30	NVO485-150 EFT40	NVO485-150 EFT60	NVO485-200 EFT60	NVO485-200 EFT90	NVO485-300 EFT90	NVOHEDP-300	Call for Sizing	Call for Sizing
8	NVO485-75 EFT20	NVO485-100 EFT30	NVO485-150 EFT60	NVO485-200 EFT60	NVO485-200 EFT60	NVO485-300 EFT90	NVO485-300	Call for Sizing	Call for Sizing	Call for Sizing
9	NVO485-75 EFT30	NVO485-150 EFT40	NVO485-150 EFT60	NVO485-200 EFT60	NVO485-300 EFT90	NVO485-300 EFT90	NVOHEDP-300	Call for Sizing	Call for Sizing	Call for Sizing
10	NVO 485-100 EFT30	NVO485-150 EFT60	NVO485-200 EFT60	NVO485-200 EFT90	NVO485-300 EFT90	NVOHEDP-300	Call for Sizing	Call for Sizing	Call for Sizing	Call for Sizing

Notes:

We recommend contacting Novo Water Customer Service for any hardness levels above 75 gpg for proper recommendations. Cabinet models are available for all 75 and 100 models.

Customer Service
1-877-288-9888

80155017 03/19