

Novo 485 and 489 Comparison Chart

	485 VALVE	489 VALVE
7-year valve warranty	✓	✓
High Efficiency Technology	Uses up to 75% less salt and 64% less water	Uses up to 75% less salt and 64% less water
Porting* (Systems come with the listed connections)	¾" porting (¾" 90-degree elbows 1" straight connectors)	1" porting (1" 90-degree elbows 1" straight connectors)
Compatible with 1" plumbing	Yes - using 1" connector	Yes
Compatible with ¾" plumbing	Yes	Yes – ¾" reducer required
Regeneration Programming	Regeneration based on # of people and water hardness programmed into the valve.	Regeneration based on programming water hardness and system's automatic, real-time calculation of daily water use.
Display	Two-line LED display	Four-line LED display
Cabinet Style	Two piece	One piece
Compatible with AIO & BIF iron filters	No	Yes

* While the 489 valve has much higher flow capability than the 485 valve, the flow capability is the same for both once assembled on a water softener or filter because the system flow rates are limited by the media and the distribution tube.



Novo 485 HTO
Softener & Carbon Filter
Combination System.



Novo 489 HTO
Softener & Carbon Filter
Combination System.
Features 1" porting.

Toll Free: 877-288-9888
www.novowater.com

Regina, SK • Cambridge, ON • Whitestown, IN
Houston, TX • Phoenix, AZ • Guadalajara, MX