

SAVE SALT, WATER & MONEY!



Hard water (calcium & magnesium) is a common problem for many homeowners and businesses. When hardness minerals are combined with heat it forms troublesome scale. Scale causes costly build-up in your plumbing, water heater and other water using appliances.

When combined with soap, the minerals form soap curd or scum that makes skin dry and itchy, hair lifeless, laundry dull and builds up on fixtures.

The NovoSoft 465 Series softener combines user friendly electronics with high efficiency technology to use less salt and water – saving you money!

NOVOSOFT 465 SERIES HIGH-EFFICIENCY WATER SOFTENER



Cabinet Model

Twin Tank Model

SOFT WATER BENEFITS

- Silky shiny hair
- Soft supple skin
- Crystal clear dishes & glassware
- Bright whites, vibrant colours
- Easier cleaning
- Use up to 75% less soap
- Lower water heating cost by 29%
- Protect plumbing & appliances
- Extend life of laundry
- Save money



NovoSoft 465 Series Water Softeners

High salt efficiency, low water use water softeners backed by the industries strongest warranty.

- Uses up to 65% less salt and 45% less water than conventional mechanical meters*



Features:

- Exclusive NovoSoft NSF Certified electronic control valve with reliable piston, seal and spacer technology
- Cabinet or Twin Tank models
- Lifetime Warranty on tanks; 7 years on valve
- Rotating "No-touch" diagnostic LCD display showing time and date, capacity, volume remaining, regeneration time, last regeneration date, current flow rate & peak flow rate
- Meter Immediate, Meter Delayed, Meter Override, Vacation and Calendar Clock mode
- Adjustable cycle times
- Tank jackets reduce condensation problems. Standard on 8", 9" and 10" models
- Brine safety valve provides extra overflow protection
- Plastic salt grid prevents salt bridging
- Unique bypass with an integrated space saving turbine meter and sample ports on the inlet. One-piece design prevents meter jamming
- Time saving quick connect fittings on bypass and brine line. Power adaptor even has quick connect for easy valve spin on
- Drain line o-ring eliminates need for Teflon
- NSF Certified fibreglass tanks
- WQA Gold Seal Approved cation resin

Item #	Model	System Capacity Grains			Flow Rate		Regeneration Water Usage (Gal)		Mineral Tank Size	Resin Cu. Ft.	Brine Tank / Cabinet Size Inches	Salt Cap Lbs	Shipping Weight Lbs
		@ 10 lbs/cu ft	@ 6 lbs/cu ft Factory Setting	@ 3 lbs/cu ft	Service USGPM	Backwash USGPM	Clean Water (Factory Setting)	Problem Water					
15010001	NVO465-75	21,000	18,750	11,550	8.0	1.5	29.5	37.0	8 x 44	0.75	18.1 x 34.5	300	84
15010002	NVO465-100	28,000	25,000	15,400	10.0	2.0	38.0	48.0	9 x 48	1.00	18.1 x 34.5	300	104
15010003	NVO465-150	42,000	37,500	23,100	12.0	2.4	48.5	60.5	10 x 54	1.50	18.1 x 34.5	300	133
15010004	NVO465-200	56,000	50,000	30,800	15.0	3.5	80.5	95.5	12 x 52	2.00	20.3 x 37.4	400	153
15010039	NVO465-300	84,000	75,000	46,200	15.0	5.0	106.5	126.5	14 x 65	3.00	20.3 x 37.4	400	220
15010005	NVO465-75C	21,000	18,750	11,550	8.0	2.0	29.5	37.0	9 x 35	0.75	16.5 x 19.3 x 43.3	300	84
15010006	NVO465-100C	28,000	25,000	15,400	10.0	2.4	38.0	48.0	10 x 35	1.00	16.5 x 19.3 x 43.3	300	104

- Voltage 12V/60Hz (120V to 12V wall mount transformer included)
- Pipe Size 3/4"
- Max Water Temp = 110°F (43°C)

- Max Operating Pressure = 100 PSIG (689 kPa)
- At stated service flow rates the pressure drop through these devices will not exceed 15 PSIG
- Do not use where microbiologically unsafe

Manufactured by:



A Division of
Canature NA
Regina, SK Kitchener, ON
www.novowater.com

Your Local Water Professional:

