

# REVERSE OSMOSIS STORAGE TANKS



## Features:

- Fully enclosed polypropylene and butyl water reservoir
- Durable steel tank
- Individually pressure tested for safety
- Meet the most demanding specifications for potable water
- Industries most comprehensive 5 year warranty
- AMTROL invented technology
- All models NSF listed
- CE
- ISO Certified

Model	Item #	Gallons	Litres	Color	Size	Material	Diameter	Height	Shipping Weight
RO-10	70020005	10 Gal	37.8 L	Blue	3/4"	Stainless Steel	15 3/8" (39.05 cm)	17 3/8" (44.13 cm)	20lbs / 9.7kg
RO-14	70020006	14 Gal	53.0 L	Blue	3/4"	Stainless Steel	15 3/8" (39.05 cm)	22 3/16" (56.36 cm)	24lbs / 10.9kg
RO-20	70020007	20 Gal	76.0 L	Blue	1"	Stainless Steel	15 3/8" (39.05 cm)	31 3/4" (80.65 cm)	32lbs / 14.6kg

		Pre-Charged Pressure 5 PSIG						
		Water Capacity in Gallons (Litres) At Various System Pressures						
PSIG		20	30	40	50	60	70	
RO-10	70020005	4.3 (16.2)	5.6 (21.1)	6.3 (23.9)	6.9 (26.1)	7.3 (27.6)	7.6 (28.7)	
RO-14	70020006	6.1 (22.9)	7.8 (29.6)	9.0 (33.9)	9.7 (36.9)	10.3 (39.0)	10.7 (40.7)	
RO-20	70020007	5.8 (21.8)	8.9 (33.9)	11.0 (41.5)	-	-	-	

Other sizes available. Contact Customer Service for details

Item #	Description
98000058	3/8" QC Ball Valve & Fittings

Quick Connect Ball Valve Assembly for use on RO-10 & 14 reduces 3/4" tank connection to John Guest Quick Connect RO ball valve 1/4" to 3/8" tubing.



Distributed by:



A Division of Canature NA  
Regina, SK . Kitchener ON  
www.novowater.com

80151014 – Aug/10

Your Local Plumbing Professional:

