

# ULTRAVIOLET FILTRATION SYSTEM



Perfect for home or cottage, this whole home UV system includes two-stage pre-filtration and UV treatment. A 20" five micron carbon block filter reduces chlorine taste & odor while a 20" ten micron sediment filter reduces particulate.

Green indication light shows normal operating conditions while a red light with audible alarm alerts the homeowner of possible system failure.

## Additional Features:

- Low maintenance
- Easy change filters
- Ready to install heavy duty racking system



Specifications VPS1140	
Rated Service Flow	30LPM / 8GPM
Unit Dimensions (L x W x H)	55.9cm/22" x 21.6cm/8.5" x 85.1cm/33.5"
Power Input	115V / 60Hz
Operating Pressure Range	0 - 100 PSI
Feed Water Temperature Range	41 – 100 -°F (5 – 37.7 °C)
Unit Volume	17L / 4.5G
Inlet Port Size	1" Female NPT
Outlet Port Size	3/4" Male NPT
Minimum distance for adjacent combustible materials	15 cm/6"

Item #	Description
40010101	8 gpm Mini UV Rack System

Manufactured by:



A Division of Canature NA  
Regina, SK . Kitchener ON  
www.novowater.com

80151013 – Aug/10

Your Local Plumbing Professional:

