

AQUA FLO[®]

PC SERIES

Pleated Cellulose Filter Cartridges

The Aqua Flo PC cartridge filters are made from pleated cellulose media and are recommended for general water filtration requirements.

FEATURES / BENEFITS:

- ◆ Pleated design maximizes filtration area for lower initial pressure drop
- ◆ Designed for general water filtration purposes
- ◆ Cellulose based material
- ◆ Available in four sizes: 2.5x10"; 2.5x20"; 4.5x10"; 4.5x20"
- ◆ Universal fit – Fits most standard water filter housings
- ◆ Available in 20 micron

SPECIFICATIONS:

- ◆ End Caps – Vinyl Plastisol
- ◆ Core – Polypropylene
- ◆ Filter Media – Cellulose paper
- ◆ Temperature Rating – 40 - 145°F (4 -63°C)

APPLICATIONS (For water filtration only):

- ◆ Commercial/Residential Drinking Water Filtration
- ◆ RO Pre-filtration
- ◆ Cooling Tower Filtration
- ◆ Chill Water Loop Filtration
- ◆ Food & Beverage Filtration
- ◆ Industrial Water Filtration



“Recommended for general water filtration requirements.”

PC SERIES

Pleated Cellulose Filter Cartridges

SPECIFICATIONS & PERFORMANCE:

ITEM #	DESCRIPTION	DIMENSIONS	CASE QTY	SHIP WEIGHT EACH (LBS)	RATING (NOMINAL)	FLOW RATE (GPM)
26276	PC-20-10	2.5" x 10" (63.5 x 254 mm)	50	0.2	20	7 US GPM (26.5 LPM)
26182	PC-20-20	2.5" x 20" (63.5 x 508 mm)	25	0.4	20	14 US GPM (52.9 LPM)
26183	PC-20-10BV	4.5" x 10" (114.3 x 254 mm)	20	0.6	20	15 US GPM (56.7 LPM)
26184	PC-20-20BV	4.5" x 20" (114.3 x 508 mm)	10	1.2	20	30 US GPM (113.4 LPM)

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

NOTE: Initial flow pressure drop less than 5 psi at rated flow rate. Change filter when pressure drop exceeds 10 psi.

AQUA FLO®

A Division of



Your Local Water Specialist