## Hydrogen Sulfide Reduction AIO Filter





Hydrogen sulfide (H2S) is a nuisance. It adds an objectionable sulfur-like taste and "rotten egg" odor to drinking water. Left untreated, it can also lead to corrosion in plumbing pipes and fixtures.

## **Features:**

- Combines aeration with catalytic carbon technology to effectively reduce sulfur from water.
- No more bad taste or odor.
- No Chemicals to buy, mix or add
- No weekly water tests to perform
- Simple, Fully Automatic regeneration with Air



IAPMO R & T Certified Against NSF/ANSI 42

	Model	Cat Carbon Cu Ft	Flow Rate USGPM			Mineral	Pipe Size	Ship			
Item #			Service	Peak	Backwash		Inches	Weight Lbs			
AIO (Air Induction Oxidizer) Filter For Hydrogen Sulfide Reduction (Single Tank)											
15010677	NVO665FAIOC-075	0.75	2	4	3.5	8 x 44	3/4"	110			
15010678	NVO665FAIOC-100	1.0	3	6	4	9 x 48	3/4"	145			
15010679	NVO665FAIOC-150	1.5	4	10	5	10 x 54	3/4"	250			

	Application Parameters							
Bed Type	Iron	Manganese	Hydrogen	pH Range				
	(ppm)	(ppm)	Sulfide (ppm)					
AIOC Catalytic Carbon	0.0	0.0	0.0 - 3.0	7.0 - 8.5				

Designed, Engineered & Assembled in the U.S.A.

Your Local Plumbing Professional

Toll Free: 877-288-9888 www.novowater.com

Regina, SK • Cambridge, ON • Whitestown, IN Houston, TX • Phoenix, AZ • Guadalajara, MX