

# AQUA FLO®

## Aqua Flo Gen H6 Residential Crossover High Flow Systems

### A Security System For Your Water

UV technology provides additional security for your water supply. It is proven to control microbiological (bacteria & virus) issues in water including ***E.coli***, ***Cryptosporidium***, and ***Giardia Lamblia*** without the use of chemicals.

### Gen H6 Residential Systems

#### Features:

- ◆ Five models available (Gen H6-5, 10, 15, 25 & 40)
- ◆ True 254nm Teflon® based UV sensor continuously measures UV output via the controller
- ◆ Color user interface with full diagnostics and warnings including QR codes
- ◆ "Future-proof" expandability port for future upgrades and options
- ◆ Axial flow, 316L stainless steel reactor
- ◆ Designed & manufactured to ASME pressure vessel standards
- ◆ Flow rates stated at 95% UVT at a dose of 30mJ/cm2
- ◆ User friendly bayonet style lamp connector (Quick ¼ turn removal. No extra tools required.)
- ◆ True gland seal retaining nut with positive stop
- ◆ Reliable, industry proven low pressure, high-output (LP-HO) coated UV lamps with ceramic bases for durability and a 10,000 hour life
- ◆ Universal input, constant current electronic controller (one controller for all systems) in a splash-proof case
- ◆ Warranty (refer to Owner's Manual)
  - Reactor Chamber - Ten (10) Year Limited
  - Electronics - Three (3) Year Limited
  - UV Lamps - One (1) Year Limited
  - Quartz Sleeves - One (1) Year Limited



#### Guidelines for Use

Parameter	Level
Hardness	< 7 gpg (120 mg/L)
Iron (Fe)	< 0.3ppm (mg/L)
Manganese (Mn)	< 0.05ppm (mg/L)
Tannins	< 0.1ppm (mg/L)
Turbidity	< 1 NTU
Transmittance (UVT)	> 75%





## AQUA FLO GEN EQUIPMENT SPECIFICATIONS

### AQUA FLO GEN H-6, Residential Crossover monitored UV systems

MODEL	GENH6-5 40030015	GENH6-10 40030016	GENH6-15 40030017	GENH6-25 40030018	GENH6-40 40030019
Flow Rate (Industry Standard)	4 GPM 15.1 lpm 0.9 m <sup>3</sup> /hr.	10 GPM 37.9 lpm 2.3 m <sup>3</sup> /hr.	14 GPM 53 lpm 3.2 m <sup>3</sup> /hr.	25 GPM <sup>2</sup> 95 lpm 5.7 m <sup>3</sup> /hr.	40 GPM 151 lpm 9.1 m <sup>3</sup> /hr.
Alternate flow @ 16 mj/cm <sup>2</sup> (US Public Health)	8 GPM 30.3 lpm 1.8 m <sup>3</sup> /hr.	19 GPM <sup>1</sup> 71.9 lpm 4.3 m <sup>3</sup> /hr.	27 GPM <sup>2</sup> 102.2 lpm 6.1 m <sup>3</sup> /hr.	47 GPM <sup>2</sup> 178 lpm 10.7 m <sup>3</sup> /hr.	78 GPM <sup>3</sup> 295 lpm 17.7 m <sup>3</sup> /hr.
Alternate flow @ 40 mj/cm <sup>2</sup> (NSF/EPA)	3 GPM 11.4 lpm 0.7 m <sup>3</sup> /hr.	7 GPM 26.5 lpm 1.6 m <sup>3</sup> /hr.	11 GPM 41 lpm 2.5 m <sup>3</sup> /hr.	19 GPM 72 lpm 4.3 m <sup>3</sup> /hr.	31 GPM 117 lpm 7 m <sup>3</sup> /hr.
Port Size	½" MNPT	¾" MNPT	1" MNPT	1" MNPT	1½" MNPT
Electrical	90-265V/50-60Hz. (IEC power cords required)				
Power Plug	North American, NEMA 5-15, 3-wire for all 110V				
Lamp Watts	18	34	45	67	101
Power (watts)	20 (19 @ 230V.)	38 (36 @ 230V.)	57 (48 @ 230V.)	73 (72 @ 230V.)	115 (108 @ 230V.)
Replacement Lamp	RL-210HO	RL-330HO	RL-420HO	RL-600HO	RL-950HO
Replacement Sleeve	RQ-210	RQ-330	RQ-420	RQ-600	RQ-950
Reactor Dimensions	3.5 x 11.7" (8.9 x 29.8 cm)	3.5 x 16.5" (8.9 x 41.8 cm)	3.5 x 20.0" (8.9 x 50.8 cm)	3.5 x 26.9" (8.9 x 68.3 cm)	3.5 x 40.7" (8.9 x 103.4 cm)
Chamber Material	316L Stainless Steel, A249 Pressure Rated Tubing, Polished & Passivated				
Controller Dimension	8.6 x 4.2 x 3.5" (217.4 x 107.5 x 88.7 mm)				
Operating Pressure	0.7-10.3 bar (10-150 psi)				
Optimum Water Temperature	2-40° C (36-104° F)				
UV Intensity Monitor	Yes				
Solenoid Output	Yes, but requires optional solenoid module				
4-20 mA Output	Yes, but requires optional 4-20 mA module				
Lamp Change Reminder (audible & visual)	Yes				
Lamp-Out Indicator (audible & visual)	Yes				
Shipping Weight	4.5 kg. (9.9 lbs.) 4 kg. (8 lbs.) cubed	5.4 kg. (11.9 lbs.) 5 kg. (11 lbs.) cubed	6.0 kg. (13.2 lbs.) 6 kg. (13 lbs.) cubed	7.2 kg. (15.9 lbs.) 8 kg. (16 lbs.) cubed	9.7 kg. (21.4 lbs.) 11 kg. (24 lbs.) cubed
<b>Note:</b> 1. based on flow velocity of 8.2 ft/sec (2.5 m/sec.), flow rate limited to <b>13.6 gpm</b> (50 lpm) (3.1 m <sup>3</sup> /hr.) for 3/4" port 2. based on flow velocity of 8.2 ft/sec (2.5 m/sec.), flow rate limited to <b>22.1 gpm</b> (84 lpm) (5.0 m <sup>3</sup> /hr.) for 1" port 3. based on flow velocity of 8.2 ft/sec (2.5 m/sec.), flow rate limited to <b>52 gpm</b> (197 lpm) (11.8 m <sup>3</sup> /hr.) for 1 ½" port					

## Sample Screens



**NSF Certified Models Available. Contact Customer Service For Details.**

### REPLACEMENT PARTS

System	Lamps	Sleeves	Controller
Aqua Flo Gen H6-5	RL-210HO #40040018	RQ-210 #40040039	RCHO-856.12 #40040074
Aqua Flo Gen H6-10	RL-330HO #40040019	RQ-330 #40040041	RCHO-856.12 #40040074
Aqua Flo Gen H6-15	RL-420HO #40040020	RQ-420 #40040042	RCHO-856.12 #40040074
Aqua Flo Gen H6-25	RL-600HO #40040021	RQ-600 #40040044	RCHO-856.12 #40040074
Aqua Flo Gen H6-40	RL-950HO #40040022	RQ-950 #40040047	RCHO-856.12 #40040074



### UV Sensor Module

Allows the 254nm UV wavelength to be measured and displayed via the GENH-6 controller. The sensor plugs directly into the controller and is mounted in the sensor port located on all GenH6 units



### Solenoid Module

Used to power a remote normally closed solenoid valve (not included). Solenoid valve will close on lamp failure or when low UV conditions are detected by the sensor. Available in 110V MOD-SOL1 (Item # 40040006)

# AQUA FLO®

Your Local Water Specialist

A Division of



80157008 03/19

www.canaturewg.com